Product Comparison



	<i>tp</i>	
Product Name	HP LaserJet Enterprise 600 Printer M602n CE991A	HP LaserJet Enterprise M608n K0Q17A
Status	Discontinued	Active
	Up to 52 ppm (Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/qo/printerclaims . Exact speed varies depending on the system configuration, software application, driver, and	
Print speed black (ISO, letter)	document complexity.)	Up to 65 ppm ⁷
Print speed duplex (letter)	Up to 35 ipm	
First page out black (letter, ready)	As fast as 8.5 sec	As fast as 5.3 sec
Duty cycle (monthly, letter)	(Duty cycle is defined as the maximumnumber of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP Laser Jet or HP Color Laser Jet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.) 3000 to 15,000	(Duty cycle is defined as the maximumnumber of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP Laser Jet or HP Color Laser Jet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.) 5000 to 25000
Recommended monthly page volume	(HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.)	(HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.)
Print languages	HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.4)	HP PCL 6, HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™
Printer Management	HP Web Jetadmin; HP SureSupply; HP Utility (Mac)	HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP Web JetAdmin Software; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver

Fonts and typefaces	105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP postscript Level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP Laser Jet Fonts and IPDS Emulation available at http://www.hp.com/go/laser jetfonts	105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); Additional font solutions available via third-party flash memory cards; HP Laser Jet Fonts and IPDS Emulation available at http://www.hp.com/go/laser jetfonts
Processor speed	800 MHz	1.2 GHz
Trocessor specu	4-line LCD (color text and	2.7-in (6.86 cm) QVGA LCD (color graphics) rotating
Display	graphics)	(adjustable angle)
HP ePrint capability	Yes	
Mobile printing capability	HP ePrint; Apple AirPrint™; Mopria™-certified	HP ePrint; Apple AirPrint™; Mopria-certified ⁶
Connectivity, standard	1 Hi-Speed USB 2.0; 1 Gigabit Ethernet; 2 External Host USB (1 walk-up and 1 external accessible); 2 internal Host USB 2.0-like ports (for 3rd party connection); 1 Hi- Speed USB 2.0 HIP (for 3rd party connection)	1 Hi-Speed Device USB 2.0; 2 Hi-Speed USB 2.0 Host; 1 Gigabit/Fast Ethernet 10/100/1000 Base-TX network; Hardware Integration Pocket
Connectivity, optional	802.11b/g/n wireless LAN (Station mode), other networking accessories; HP Jetdirect 2700w USB Wireless Print Server (available in early 2012)	HP Jetdirect 2900nw Print Server J8031A; HP Jetdirect 3000w NFC/Wireless Accessory J8030A
3 , 3 , 1	Standard (built-in Gigabit	,
Network ready	Ethernet)	
Maximum Memory	1 GB	1.5 GB, MAX memory, when 1GB Accessory DIMM is installed
Memory card compatibility	USB Flash drive	
Internal Storage	Standard, 8 GB Solid State Drive (SSD)	Optional, 500 GB (with accessory B5L29A)
Input capacity	Up to 600 sheets	Up to 650 sheets
Maximum input capacity (sheets)	Up to 3600 sheets Up to 600 sheets (500 in the face down bin, 100 in rear	Up to 4400 sheets
Output capacity	face up door) Up to 1100 sheets (Rear face- up door: up to 100 sheets; Top output bin: up to 500 sheets; optional 5-bin mailbox, optional stacker, optional stapler/stacker: up	Up to 500 sheets
Maximum output capacity (sheets)	to 500 sheets)	Up to 1300 sheets
Envelope Feeder	Yes, 75	Yes, 75 (optional)
Madio sino supersidad	Multipurpose tray 1: letter, legal, executive, statement, 8.5 x 13 in, 3 x 5 in, 4 x 6 in, 5 x 7 in, 5 x 8 in, envelope (commercial No. 9, No. 10, Monarch), US postcard; Tray 2, optional 500-sheet input tray: letter, legal, executive, 8.5 x 13 in; optional 1500-sheet High-capacity input tray letter, legal.	feeder 1: Letter, legal, statement, executive, Oficio (8.5 x 13 in), envelopes [No. 9, No. 10, Monarch (7 3/4)], 3 x 5, 4 x 6, 5 x 7, 5 x 8; feeder 2:
Media sizes supported	tray: letter, legal	letter, executive, legal
Media sizes, custom	Multipurpose tray 1: 3 x 5 to 8.5 x 14 in; Tray 2, optional 500-sheet input tray: 5.83 x 8.27 to 8.5 x 14 in; Optional Custommedia cassette: 4.02 x 5.83 to 6.69 x 11.10 in	feeder 1: 3 x 5 to 8.5 x 14 in; feeder 2: 3.90 x 5.83 to 8.5 x 14 in
	Paper (bond, color,	Paper (plain, light, bond, recycled, heavy, extra heavy,
Media types	letterhead, plain, preprinted, prepunched, recycled, rough, light); envelopes; labels; cardstock; transparencies; shelf edge labels; user- defined	cardstock, pre-printed, pre- punched, colored, rough, heavy rough), mono transparency, labels, letterhead, envelope, heavy envelope

Media weight, supported	Multipurpose tray 1: 16 to 53 lb; Tray 2, optional 500-sheet input tray, optional Custom media cassette, optional 1500-sheet High-capacity input tray: 16 to 32 lb; Optional Envelope feeder: 20 to 28 lb; Optional Duplexer: 16 to 32 lb 110-volt input voltage: 100 to 127 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz) (Not dual voltage, power supply varies by part number with # Option code identifier)	Feeder 1: 16 to 53 lb bond (plain), 16 to 24 lb (envelopes); feeder 2: 16 to 32 lb bond (plain) 100V - 127V nominal @ +/- 10% (min 90V, max 140V); 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 12 A; 220V - 240V nominal, @ +/-10% (min 198V, Max 264V); 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 6 A
Power supply type	Internal (Built-in) power supply	Built in 115V or 220V Power Supply (Not dual voltage, power supply varies by part number with # Option code identifier)
Power consumption	820 watts (Printing), 21 watts (Ready), 5.5 watts (Sleep), 1.0 watt (Auto-Off), 0.3 watts (Manual-Off) (Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages; this will damage the printer and void the product warranty. Power consumption in Auto-Off mode depends on customer network switch capability, user configuration and network activity. Off-mode power may vary while checking network packets for print jobs.)	780 watts (printing), 15.3 watts (ready), 3.1 watts (sleep), < 0.1 watts (Auto Off/Manual On), < 0.1 watts (Manual Off) ³
Power consumption (active)	820 watts	
Energy efficiency	CECP	
Minimum dimensions (W x D x H)	16.3 x 16.9 x 15.7 in	17 x 18.3 x 15 in
Maximum dimensions (W x D x H)	16.3 x 30.2 x 15.7 in	17 x 40.9 x 17.8 in
Weight	52.1 lb	47.7 lbs
Package dimensions (W x D x H)	23.15 x 21.26 x 19.65 in	23.50 x 19.57 x 21.22 in
Package weight	60.5 lb	60.1 lb
Pallet dimensions	40 × 48 × 90 in	47.24 x 39.37 x 90.94 in (AP), 47.24 x 39.37 x 91.33 in (EMEA & AMS)
Pallet weight	1018 lb	955.89 lb (NA, EMEA, AP)

HP LaserJet Enterprise 600 Printer M602n(CE991A)

© Copyright 2011 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing shall be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

HP LaserJet Enterprise M608n(K0Q17A)

- 3 Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty.
- ${\small 6}\quad {\small May\ require\ a\ firmware\ upgrade\ to\ be\ compatible,\ download\ at\ \underline{http://www.hp.com/go/support}}$
- 7 Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

© Copyright 2017 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing shall be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.